

TECHNICAL DATA SHEET

PROTECTIVE TAPE

BT 955

APPLICATIONS

Temporary protection of carpets and moquettes.

STORAGE AND UTILIZATION

The tape can be stored for six months at room temperature , in dry conditions and in its original packaging.

OUTLINES

UNIT

FILM TYPE		Polyethylene(LDPE)
AVERAGE THICKNESS (AFERA 4006-Ed. 9/79)	micron	100
COLOUR		Clear or Blue
ADHESIVE TYPE		Acrylic solvent base
ADHESION TO STEEL (AFERA 4001-Ed. 10/87)	cN/cm	400
LONGITUDINAL TENSILE STRENGTH (AFERA 4004-Ed. 9/79)	daN/cm	> 1,9
TRANSVERSAL TENSILE STRENGTH (AFERA 4004-Ed. 9/79)	daN/cm	> 1,5
LONGITUDINAL MAX. ELONGATION (AFERA 4005-Ed. 9/79)	%	> 370
TRANSVERSAL MAX. ELONGATION (AFERA 4005-Ed. 9/79)	%	> 550

Note : A.F.E.R.A. = Association des Fabricants Européens de Rubans Auto-Adhésifs.

The figures above mentioned are means of test results and cannot be deemed as product specification.
It remains at all time customers' responsibility to ensure that BOSTON tapes products are suitable for their own purposes.

It is understood that no responsibility attaches to BOSTON tapes for an incorrect utilization of its products.
Warranty is limited on replacement of products supplied and proved to be defective with the exclusion of any other indemnity , other damages or interests.

Issuing date :February 97

Supersedes February 1996 issue.